

RIOCORD

DETONATING CORD



RIOCORD is a flexible detonating cord with a core made of an explosive material (PETN). RIOCORD detonates at an approximate speed of 7,500 m/s.


RIOCORD, when used correctly, can initiate packaged explosives and RIOBOOSTER. RIOCORD can also be used as a trunkline to initiate non electric detonators or with RIODELAY micro delay relays, making for a wide variety of sequencing possibilities.

RIOCORD is manufactured in three series, permissible, reinforced and standard.

Permissible RIOCORD is manufactured with 6 g/m and a coating that includes a delay agent in its composition, making it suitable for use in underground coal mining.

RIOCORD reinforced cords are used in extreme conditions where special features such as extremely high tensile strength and abrasion resistance are required.

RIOCORD 80 and RIOCORD 100 are used in shape blasting (presplitting and contour blasting).



1. Reinforced cords with higher tensile strength and abrasion resistance.



2. Colour coded for fast identification of cord.

Advantages

- Safe, reliable and user friendly.
- Excellent resistance to oil and water penetration.
- Colour coded for fast, easy identification.
- Good flexibility and secure knot holding.

The entire RIOCORD range is oil and water resistant and flexible. RIOCORD must be initiated with a #8 strength detonator or another line of RIOCORD. Recommended connection is explained on the instruction sheet and should always be followed.

It is essential that the detonating cord be checked to ensure that it is dry at the initiation location.

Standard RIOCORD, Class 1.1D (nominal values)

Type	PETN Coreload (g/m)	Colour	Diameter (mm)	Min. Tensile Resistance (kg)	Packaging rolls x length (m)	Net Weight (kg)	Gross Weight (kg)	Applications
PV 6	6	Fuchsia	3,6	60	2x400 or 4x200	10,6/10,6	12,0/12,2	Trunk line for non electric systems.
PV 10	10	Red	4,0	75	2x250 or 4x125	10,0/10,0	11,4/11,6	Throughout the borehole to initiate non electric system. Trunk line cable
PV 12	12	Blue	4,4	75	2x250 or 4x125	11,0/11,0	12,4/12,6	Throughout the borehole to initiate non electric system. Trunk line cable
PV 20	20	White	5,7	100	2x200 or 4x100	13,6/13,6	15,0/15,2	Throughout the borehole to initiate non electric system. Trunk line cable
PV 40	40	Green	7,8	100	2x100	12,6	14,0	Throughout the borehole to initiate non electric system. Trunk line cable
PV 80	80	Yellow	10,3	70	2x50	12,5	14,0	Contour blasting
PV 100	100	Red	11,2	70	2x50	12,6	14,0	Contour blasting

Reinforced RIOCORD, Class 1.1D (nominal values)


RF 3	3	Red with two Blue lines	3,6	75	2x400 or 4x200	9,6/9,6	11,0/11,2	Inside boreholes to initiate high-power explosives
RF 6	6	Yellow with two Red lines	3,8	90	2x350	9,6	11,0	Inside borehole and trunk line cable. Excellent mechanical characteristics
RF 10	10	White with two Green lines	5,0	100	2x250	10,6	12,0	Throughout the borehole to initiate non electric system. Trunk line cable
RF 15	15	Green with two Black lines	5,7	100	2x200	12,6	14,0	Throughout the borehole to initiate non electric system. Trunk line cable Underwater application.

Permissible RIOCORD, Class 1.1D (nominal values)

PS	6	Yellow	7,5	40	2x100	18,6	20	For use in potentially explosive atmospheres
----	---	--------	-----	----	-------	------	----	--

Contact your local MAXAM representative for further information.

Transport Classification	Standard Packaging
Class	1.1D
UN Number	UN 0065



SAFETY WARNING

Read the Instructions Safety Sheet and the Material Safety Data Sheet provided carefully before using RIOCORD. With the exception of permissible RIOCORD, RIOCORD must not be used in flammable environments such as methane or coal dust. MAXAM strongly recommends not to use RIOCORD products with detonators and/or initiation systems supplied by other manufacturers in the same blast and declines all responsibility in these cases.

RIOCORD must be stored at moderate temperatures in a dry and well ventilated place.

LEGAL WARNING AND EXCLUSION OF RESPONSIBILITY

The information contained herein (the "Information") is not exhaustive and subject to periodical review. The data contained herein may vary on account of the particular operating and maintenance conditions and of external factors, such as humidity, temperature, or pressure. Maxam Europe, S.A. and/or its affiliates ("MAXAM") do not warrant or make any representation regarding the accuracy or completeness of the Information. MAXAM further reserves the right, in its sole discretion and without prior written notice, to modify the products described herein (the "Products") and/or their specifications.

The use of the Products is an intrinsically dangerous activity and must, consequently, be restricted to qualified and trained users in possession of any necessary permits and licenses, and comply at all times with appropriate safety and risk prevention measures and with the applicable law. The use, storage, or otherwise handling, of the Products may be subject to local regulations and restrictions, which must be examined and observed by the user.

This document and any accompanying information (the "Documentation") is not intended to constitute, and shall not be construed as, an offer or contractual commitment on MAXAM's side. MAXAM expressly disclaims any liability towards third parties with regard to the Documentation. For further information about the Products, please contact your distributor or sales representative directly.

Distributor:

MAXAM Europe, S.A.
Avda. del Partenón, 16
Campo de las Naciones
28042 Madrid, SPAIN
Tel: +34 91 722 01 00
Fax: +34 91 722 01 01